

SONORAN

ST TIRES



OFFERING & SPECIFICATIONS

- » Dual compound construction for longer tread life and reduced rolling resistance, improved fuel economy
- » Specialized tread pattern
- » Provides improved towing stability in all weather conditions
- » Superior quality maintained through 100% in-line automated uniformity testing
- » 6 Year Warranty
- » 1 Year, Hassle-Free Replacement
- » Dexter Defender Roadside Assistance Package

Size	Load Range	Ply Rating	Load Capacity		Speed Rating	Tread Depth	Tire Construction*	
			Single	Dual			Sidewall	Tread
ST175/80R13	C	6	1360 lbs/50 psi	N/A	N (87 mph)	7/32"	1P	1P+2S+1N
ST175/80R13	D	8	1610 lbs/65 psi	N/A	N (87 mph)	7/32"	1P	1P+2S+1N
ST185/80R13	C	6	1480 lbs/50 psi	N/A	N (87 mph)	7/32"	1P	1P+2S+1N
ST205/75R14	C	6	1760 lbs/50 psi	N/A	N (87 mph)	7/32"	1P	1P+2S+1N
ST205/75R14	D	8	2040 lbs/65 psi	N/A	N (87 mph)	7/32"	2P	2P+2S+1N
ST215/75R14	D	8	2200 lbs/65 psi	N/A	N (87 mph)	7/32"	2P	2P+2S+1N
ST205/75R15	C	6	1820 lbs/50 psi	N/A	N (87 mph)	7/32"	1P	1P+2S+1N
ST205/75R15	D	8	2150 lbs/65 psi	N/A	N (87 mph)	7/32"	2P	2P+2S+1N
ST225/75R15	D	8	2540 lbs/65 psi	N/A	N (87 mph)	7/32"	2P	2P+2S+1N
ST225/75R15	E	10	2860 lbs/80 psi	N/A	N (87 mph)	7/32"	2P	2P+2S+1N
ST235/80R16	E	10	3520 lbs/80 psi	3080 lbs/80 psi	N (87 mph)	7/32"	2P	2P+2S+1N
ST235/80R16	G	14	4080 lbs/110 psi	3640 lbs/110 psi	M (81 mph)	11/32"	1S	4S
ST235/85R16	G	14	4400 lbs/110 psi	3860 lbs/110 psi	M (81 mph)	11/32"	1S	4S
215/75R17.5	H	16	4805 lbs/123 psi	4540 lbs/123 psi	M (81 mph)	12/32"	1S	4S
235/75R17.5	J	18	6005 lbs/127 psi	5675 lbs/127 psi	M (81 mph)	13/32"	1S	4S

* Tire Construction Abbreviations: P = Polyester; S = Steel; N = Nylon

dextergroup.com

© 2005-2026 Dexter Axle Company | LIT-311-00 | 2026.01

