

GOODRIDE TIRES



OFFERING & SPECIFICATIONS

- » Thick construction provides for reliable towing and braking
- » Double steel belt construction to counteract heat cycle damage, expanding and contracting, and provide towing stability under load
- » Puncture resistant with full nylon cap construction
- » Heatless compound technology to slow down the aging of the tire and extend life
- » Tread depth provides low rolling resistance reducing tread wear and improving fuel economy
- » 6 Year Warranty and 1 Year, Hassle-Free Replacement
- » Dexter Defender Roadside Assistance

| Size | Load Range | Ply Rating | Load Capacity | | Speed Rating | Tread Depth | *Tire Construction | |
|-------------|------------|------------|------------------|------------------|--------------|-------------|--------------------|----------|
| | | | Single | Dual | | | Sidewall | Tread |
| ST145R12 | E | 10 | 1520 lbs/80 psi | N/A | M (81 mph) | 7/32" | 2P | 2P+2S+1N |
| ST175/80R13 | C | 6 | 1360 lbs/50 psi | N/A | M (81 mph) | 8/32" | 1A | 1A+2S+1N |
| ST175/80R13 | D | 8 | 1615 lbs/65 psi | N/A | M (81 mph) | 8/32" | 2A | 2A+2S+1N |
| ST185/80R13 | D | 8 | 1760 lbs/65 psi | N/A | M (81 mph) | 8/32" | 2A | 2A+2S+1N |
| ST205/75R14 | C | 6 | 1760 lbs/50 psi | N/A | M (81 mph) | 8/32" | 1A | 1A+2S+1N |
| ST205/75R14 | D | 8 | 2040 lbs/65 psi | N/A | M (81 mph) | 8/32" | 2A | 2A+2S+1N |
| ST205/75R15 | C | 6 | 1820 lbs/50 psi | N/A | M (81 mph) | 8/32" | 1A | 1A+2S+1N |
| ST205/75R15 | D | 8 | 2150 lbs/65 psi | N/A | M (81 mph) | 8/32" | 2A | 2A+2S+1N |
| ST225/75R15 | D | 8 | 2540 lbs/65 psi | N/A | M (81 mph) | 9/32" | 2P | 2P+2S+1N |
| ST225/75R15 | E | 10 | 2830 lbs/80 psi | N/A | M (81 mph) | 9/32" | 2P | 2P+2S+1N |
| ST235/80R16 | E | 10 | 3520 lbs/80 psi | 3080 lbs/80 psi | M (81 mph) | 9/32" | 2P | 2P+2S+1N |
| ST235/85R16 | F | 12 | 3960 lbs/95 psi | 3520 lbs/95 psi | M (81 mph) | 9/32" | 2P | 2P+2S+1N |
| ST235/80R16 | G | 14 | 4080 lbs/110 psi | 3640 lbs/110 psi | L (75 mph) | 9/32" | 1S | 4S |
| ST235/85R16 | G | 14 | 4400 lbs/110 psi | 3860 lbs/110 psi | L (75 mph) | 10/32" | 1S | 4S |
| 215/75R17.5 | H | 16 | 4850 lbs/123 psi | 4540 lbs/123 psi | L (75 mph) | 12/32" | 1S | 4S |
| 235/75R17.5 | J | 18 | 6005 lbs/128 psi | 5675 lbs/128 psi | L (75 mph) | 13/32" | 1S | 4S |

*Tire Construction Abbreviations: A = Polyamide; P = Polyester; S = Steel; N = Nylon

www.dexteraxle.com

© 2005-2023 Dexter Axle Company | LIT-312-00 | 2023.10

